



	MATERIAL
①	N-BAF10
②	N-SF6HT



NOTES/SPECIFICATIONS:

- DESIGN WAVELENGTHS: 486.1nm, 587.6nm, & 656.3nm
- FOCAL LENGTH: $f=30.0\text{mm} \pm 1\%$ AT 587.6nm
- BACK FOCAL LENGTH (REF): 22.2mm
- CLEAR APERTURE $> 22.86\text{mm}$
- SURFACE QUALITY: 40-20 SCRATCH-DIG
- CENTRATION: $< 3\text{arcmin}$
- DIAMETER TOLERANCE: $+0.0/-0.1\text{mm}$
- THICKNESS TOLERANCE: $\pm 0.10\text{mm}$
- COATING: BBAR $R_{\text{avg}} < 0.5\%$ FROM 400-700nm, 0 AOI, ON OUTER OPTICAL SURFACES

FOR INFORMATION ONLY
NOT FOR MANUFACTURING PURPOSES

DRAWING PROJECTION						
	NAME	DATE	D25.4mm, F=30.0mm, Visible Achromat			
DRAWN	CWD	2022/5/18	AD254-30-A			
APPROVAL	ZSE	2022/5/18	MATERIAL	WEIGHT	SCALE	REV
FOR INFORMATION ONLYNOT FOR MANUFACTURING PURPOSES			SEE TABLE	0.02089Kg	2:1	A