



## **NOTES/SPECIFICATIONS:**

- DESIGN WAVELENGTH: 587.6nm
  FOCAL LENGTH: 150.0mm±1%
  BACK FOCAL LENGTH (REF): 147.5mm
  CLEAR APERTURE: ≥90% OF DIAMETER
  SURFACE QUALITY: 20-10 SCRATCH-DIG

- 2. 3. 4. 5. 6. 7. 8. 9. SURFACE QUALITY: 20-10 SCRATCH-DIG CENTRATION: <3 arcmin DIAMETER TOLERANCE: +0.0/-0.1 mm THICKNESS TOLERANCE: ±0.1 mm COATING: BBAR Ravg <0.5% FROM 1050-1700nm, 0° AOI, ON OUTER OPTICAL SURFACES DIFFRACTION LIMITED DIAMETER @632.8 nm: 13.5 mm DIFFRACTION LIMITED DIAMETER @1064 nm: 16.0 mm
- 10.
- 11.

## FOR INFORMATION ONLY NOT FOR MANUFACTURING PURPOSES

DRAWING PROJECTION	$\bigcirc \bigcirc$		客创光科 RCOPTICS			
	NAME	DATE	D25. 4, F=150. 0, N-	-BK7, C Coate	d, Best F	orm Lens
DRAWN	CWD	2022/5/18	BFBX1254-150-C			
APPROVAL	ZSB	2022/5/18	MATERIAL	WEIGHT	SCALE	REV
FOR INFORMATION ONLYNOT FOR MANUFACTURING PURPOSES			N-BK7	0.02kg	1:1	A