



SECTION A-A

#### NOTES/SPECIFICATIONS:

- DESIGN WAVELENGTH: 587.6nm
- FOCAL LENGTH:  $f=15.0\text{mm} \pm 1\%$
- BACK FOCAL LENGTH(REF):  $bf=13.3\text{mm}$
- CLEAR APERTURE:  $>90\%$
- SURFACE QUALITY: 40-20 SCRATCH-DIG
- CENTRATION:  $<3\text{arcmin}$
- DIAMETER TOLERANCE:  $+0.0/-0.1\text{mm}$
- THICKNESS TOLERANCE:  $\pm 0.1\text{mm}$
- COATING: BBAR  $R_{avg} < 0.5\%$  FROM 350nm-700nm,  $0^\circ$  AOI, ON OUTER OPTICAL SURFACES

ALL DIMENSIONS ARE IN THE FORM  $\frac{[in]}{mm}$

THIS DRAWING IS FOR INFORMATION ONLY  
NOT INTENDED FOR MANUFACTURING

DRAWING PROJECTION						
	NAME	DATE	D12.7 F=15.0 N-BK7 A Coated Bi Convex Lens			
DRAWN	CWD	2022/5/18	BX1127-15-A			
APPROVAL	ZSB	2022/5/18	MATERIAL	WEIGHT	SCALE	REV
FOR INFORMATION ONLYNOT FOR MANUFACTURING PURPOSES			N-BK7		4:1	A