





SECTION A-A

NOTES/SPECIFICATIONS:

- DESIGN WAVELENGTH: 587.6nm
- FOCAL LENGTH: $f=19.9\text{mm} \pm 1\%$
- BACK FOCAL LENGTH(REF): $bf=18.6\text{mm}$
- CLEAR APERTURE: $>90\%$
- SURFACE QUALITY: 40-20 SCRATCH-DIG
- CENTRATION: $<3\text{arcmin}$
- DIAMETER TOLERANCE: $+0.0/-0.1\text{mm}$
- THICKNESS TOLERANCE: $\pm 0.1\text{mm}$
- COATING: BBAR $R_{\text{avg}} < 0.5\%$ FROM 350nm-700nm, 0° AOI, ON OUTER OPTICAL SURFACES

ALL DIMENSIONS ARE IN THE FORM $\frac{\text{[in]}}{\text{mm}}$

THIS DRAWING IS FOR INFORMATION ONLY
NOT INTENDED FOR MANUFACTURING

DRAWING PROJECTION						
	NAME	DATE	D12.7 F=20.0 N-BK7 A Coated Bi Convex Lens			
DRAWN	CWD	2022/5/18	EX1127-20-A			
APPROVAL	ZSE	2022/5/18	MATERIAL	WEIGHT	SCALE	REV
FOR INFORMATION ONLYNOT FOR MANUFACTURING PURPOSES			N-BK7		4:1	A