



SECTION A-A

NOTES/SPECIFICATIONS:

1. DESIGN WAVELENGTH: 587.6nm
2. FOCAL LENGTH: $f=996.7\text{mm} \pm 1\%$
3. BACK FOCAL LENGTH(REF): $bf=995.5\text{mm}$
4. CLEAR APERTURE: $>90\%$
5. SURFACE QUALITY: 40-20 SCRATCH-DIG
6. CENTRATION: $<3\text{arcmin}$
7. DIAMETER TOLERANCE: $+0.0/-0.1\text{mm}$
8. THICKNESS TOLERANCE: $\pm 0.1\text{mm}$
9. COATING: BBAR Ravg<0.5% FROM 650nm-1050nm, 0° AOI, ON OUTER OPTICAL SURFACES

[in]

ALL DIMENSIONS ARE IN THE FORM mm.

THIS DRAWING IS FOR INFORMATION ONLY
NOT INTENDED FOR MANUFACTURING

DRAWING PROJECTION			RCOPTICS			
	NAME	DATE	D50.8 F=1000.0 N-BK7 B Coated Bi Convex Lens			
DRAWN	CWD	2022/5/18	EX1508-1000-B			
APPROVAL	ZSB	2022/5/18	MATERIAL	WEIGHT	SCALE	REV
FOR INFORMATION ONLY NOT FOR MANUFACTURING PURPOSES				N-BK7	1:1	A