



## NOTES/SPECIFICATIONS:

- 1. DESIGN WAVELENGTH: 587.6 nm
- 2. FOCAL LENGTH: f=250.9 mm ± 1%
- 3. BACK FOCAL LENGTH(REF): bf=249.9 mm
- 4. CLEAR APERTURE:  $> \emptyset$  22.86 mm
- 5. SURFACE QUALITY: 40-20 SCRATCH-DIG
- 6. CENTRATION: ≤ 3 arcmin
- 7. DIAMETER TOLERANCE: +0.0/-0.1 mm
- 8. THICKNESS TOLERANCE: ±0.1 mm
- 9. COATING(\$1,\$2): BBAR Ravg<0.5% FROM 1050-1700 nm, 0° AOI

FOR INFORMATION ONLY NOT FOR MANUFACTURING PURPOSES

DRAWING PROJECTION			<b>PROPTICS</b>			
	NAME	DATE	F= 250.0 mm, D25.4 UV Fused Silica Bi-Convex Lens, C Coateding			
DRAWN	CWD	2022/5/18	BX4254-250-C			
APPROVAL	ZSB	2022/5/18	MATERIAL	WEIGHT	SCALE	REV
FOR INFORMATION ONLYNOT FOR MANUFACTURING PURPOSES			UV FUSED SILICA	0.00261kg	1:1	A