



NOTES/SPECIFICATIONS:

1. DESIGN WAVELENGTH: 587.6 nm
2. FOCAL LENGTH: $f=40.1\text{ mm} \pm 1\%$
3. BACK FOCAL LENGTH(REF): $bf=37.8\text{ mm}$
4. CLEAR APERTURE: $> \Phi 22.86\text{ mm}$
5. SURFACE QUALITY: 40-20 SCRATCH-DIG
6. CENTRATION: $\leq 3\text{ arcmin}$
7. DIAMETER TOLERANCE: $+0.0/-0.1\text{ mm}$
8. THICKNESS TOLERANCE: $\pm 0.1\text{ mm}$
9. COATING(S1,S2): BBAR $R_{avg}<0.5\%$ FROM 1050-1700 nm, 0° AOI

FOR INFORMATION ONLY
NOT FOR MANUFACTURING PURPOSES

DRAWING PROJECTION						
	NAME	DATE	F= 40.0 mm, D25.4 UV Fused Silica Bi-Convex Lens, C Coateding			
DRAWN	CWD	2022/5/18	EX4254-40-C			
APPROVAL	ZSB	2022/5/18	MATERIAL	WEIGHT	SCALE	REV
FOR INFORMATION ONLYNOT FOR MANUFACTURING PURPOSES			UV FUSED SILICA	0.00486kg	1:1	A