





Notes/Specifications:

1. Design wavelength: 780nm
2. Clear aperture: >80% of length and width
3. Transmitted wavefront error: $< \lambda / 4$ @ 633nm
4. Surface flatness: $< \lambda / 4$ @ 633nm
5. Surface quality (S1-S4): 20-10 scratch-dig
6. Transmitted beam deviation: < 5 arcmin
7. Reflected beam deviation: $90^\circ \pm 5$ arcmin
8. Extinction ratio: $T_p/T_s > 3000:1$
9. Transmission efficiency: $T_p > 95\%$
10. Reflection efficiency: $R_s > 99.5\%$
11. Coating (S1-S4):
VAR coating $R_{abs} < 0.25\%$ @ 780nm, 0° AOI



FOR INFORMATION ONLY
NOT FOR MANUFACTURING PURPOSES

DRAWING PROJECTION						
	NAME	DATE	12.7mm Polarizing Beamsplitter Cube, 780nm			
DRAWN	CWD	2022/5/18	PBS127-780			
APPROVAL	ZSB	2022/5/18	MATERIAL	WEIGHT	SCALE	REV
FOR INFORMATION ONLYNOT FOR MANUFACTURING PURPOSES			UV FUSED SILICA	0.0045kg	5:1	A