



- NOTES/SPECIFICATIONS:

 1. DESIGN WAVELENGTH: 587.6nm

 2. FOCAL LENGTH: f= -6.0mm ± 1%

 3. BACK FOCAL LENGTH(REF): bf= -6.8mm

 4. CLEAR APERTURE: >90%

 5. SURFACE QUALITY: 40-20 SCRATCH-DIG

 6. CENTRATION: <3arcmin

 7. DIAMETER TOLERANCE: +0.0/-0.1mm

 8. THICKNESS TOLERANCE: ±0.1mm

 9. COATING: BRAR ROYG<0.5% FROM 650ng COATING: BBAR Rayg<0.5% FROM 650nm-1050nm, 0° AOI, ON OUTER OPTICAL SURFACES

ALL DIMENSIONS ARE IN THE FORM $\frac{[in]}{mm}$

THIS DRAWING IS FOR INFORMATION ONLY NOT INTENDED FOR MANUFACTURING

DRAWING PROJECTION	$\bigcirc \bigcirc$		客创光科 RCOPTICS			
	NAME	DATE	D6. 0 F= -6. 0 N-SF11	B Coated Pla	no Concav	re Lens
DRAWN	CWD	2022/5/18	PC20066-B			
APPROVAL	ZSB	2022/5/18	MATERIAL	WEIGHT	SCALE	REV
FOR INFORMATION ONLYNOT FOR MANUFACTURING PURPOSES			N-SF11		8:1	С