




NOTES/SPECIFICATIONS:

- DESIGN WAVELENGTH: 587.6 nm
- FOCAL LENGTH: $f = -10.0 \text{ mm} \pm 1\%$
- BACK FOCAL LENGTH(REF): $bf = -11.4 \text{ mm}$
- CLEAR APERTURE: $> \varnothing 5.4 \text{ mm}$
- SURFACE QUALITY: 40-20 SCRATCH-DIG
- CENTRATION: $\leq 3 \text{ arcmin}$
- DIAMETER TOLERANCE: $+0.0/-0.1 \text{ mm}$
- THICKNESS TOLERANCE: $\pm 0.1 \text{ mm}$
- SURFACE IRREGULARITY: $\leq \lambda/4, @633 \text{ nm}$
- PLANO SURFACE FLATNESS: $\leq \lambda/2, @633 \text{ nm}$
- SPHERICAL SURFACE POWER: $\leq 3\lambda/2, @633 \text{ nm}$
- COATING(S1,S2): BBAR $R_{avg} < 0.5\%$ FOR 1050 nm-1700 nm, 0° AOI

FOR INFORMATION ONLY
NOT FOR MANUFACTURING PURPOSES

DRAWING PROJECTION						
	NAME	DATE	UVFS PCC Lens, D6mm, F= -10 mm, C Coated			
DRAWN	CWD	2022/5/18	PC4006--10-C			
APPROVAL	ZSB	2022/5/18	MATERIAL	WEIGHT	SCALE	REV
FOR INFORMATION ONLYNOT FOR MANUFACTURING PURPOSES			UV FUSED SILICA	0.0001kg		A