





SECTION A-A

NOTES/SPECIFICATIONS:

- DESIGN WAVELENGTH: 587.6 nm
- FOCAL LENGTH: $f=-100.3\text{ mm} \pm 1\%$
- BACK FOCAL LENGTH(REF): $bf=-102.7\text{ mm}$
- CLEAR APERTURE: $> \phi 11.43\text{ mm}$
- SURFACE QUALITY: 40-20 SCRATCH-DIG
- CENTRATION: $\leq 3\text{ arcmin}$
- DIAMETER TOLERANCE: $+0.0/-0.1\text{ mm}$
- THICKNESS TOLERANCE: $\pm 0.1\text{ mm}$
- SURFACE IRREGULARITY: $\leq \lambda/4, @633\text{ nm}$
- PLANO SURFACE FLATNESS: $\leq \lambda/2, @633\text{ nm}$
- SPHERICAL SURFACE POWER: $\leq 3\lambda/2, @633\text{ nm}$
- COATING(S1,S2): BBAR $R_{avg}<0.5\%$ FOR 350 nm-700 nm, 0° AOI

FOR INFORMATION ONLY
NOT FOR MANUFACTURING PURPOSES

DRAWING PROJECTION							
	NAME	DATE	UVFS PCC Lens, D12.7, F= -100 mm, A Coated				
DRAWN	CWD	2022/5/18	PC4127--100-A				
APPROVAL	ZSB	2022/5/18	MATERIAL	WEIGHT	SCALE	REV	
FOR INFORMATION ONLYNOT FOR MANUFACTURING PURPOSES			UV FUSED SILICA	0.001kg		A	