



SECTION A-A

NOTES/SPECIFICATIONS:

- DESIGN WAVELENGTH: 587.6 nm
- FOCAL LENGTH:  $f = -25.1 \text{ mm} \pm 1\%$
- BACK FOCAL LENGTH(REF):  $bf = -27.1 \text{ mm}$
- CLEAR APERTURE:  $> \varnothing 11.43 \text{ mm}$
- SURFACE QUALITY: 40-20 SCRATCH-DIG
- CENTRATION:  $\leq 3 \text{ arcmin}$
- DIAMETER TOLERANCE:  $+0.0/-0.1 \text{ mm}$
- THICKNESS TOLERANCE:  $\pm 0.1 \text{ mm}$
- SURFACE IRREGULARITY:  $\leq \lambda/4$ , @633 nm
- PLANO SURFACE FLATNESS:  $\leq \lambda/2$ , @633 nm
- SPHERICAL SURFACE POWER:  $\leq 3\lambda/2$ , @633 nm
- COATING(S1,S2): BBAR  $\text{Ravg} < 0.5\%$  FROM 1050 nm-1700 nm,  $0^\circ$  AOI

FOR INFORMATION ONLY  
NOT FOR MANUFACTURING PURPOSES

DRAWING PROJECTION						
	NAME	DATE	D12.7mm F=-25mm UVFS C Coated Plano Concave Lens			
DRAWN	CWD	2022/5/18	PC4127--25-C			
APPROVAL	ZSB	2022/5/18	MATERIAL	WEIGHT	SCALE	REV
FOR INFORMATION ONLYNOT FOR MANUFACTURING PURPOSES			UV GRADE FUSED SILICA	0.0011kg		C