



SECTION A-A

NOTES/SPECIFICATIONS:

1. DESIGN WAVELENGTH: 587.6 nm
2. FOCAL LENGTH: $f = -30.1 \text{ mm} \pm 1\%$
3. BACK FOCAL LENGTH(REF): $bf = -32.2 \text{ mm}$
4. CLEAR APERTURE: $> \text{Ø } 11.43 \text{ mm}$
5. SURFACE QUALITY: 20-10 SCRATCH-DIG
6. CENTRATION: $\leq 3 \text{ arcmin}$
7. DIAMETER TOLERANCE: $+0.0/-0.1 \text{ mm}$
8. THICKNESS TOLERANCE: $\pm 0.1 \text{ mm}$
9. SURFACE IRREGULARITY: $\leq \lambda/4$, @633 nm
10. PLANO SURFACE FLATNESS: $\leq \lambda/2$, @633 nm
11. SPHERICAL SURFACE POWER: $\leq 3\lambda/2$, @633 nm
12. COATING(S1,S2): VAR R<0.25% PER SURFACE FOR 1064 nm, 0° AOI

FOR INFORMATION ONLY
NOT FOR MANUFACTURING PURPOSES

DRAWING PROJECTION							
	NAME	DATE	UVFS PCC Lens,D12.7,F= -30 mm,1064 nm V-Coating				
DRAWN	CWD	2022/5/18	PC4127--30-1064				
APPROVAL	ZSB	2022/5/18	MATERIAL	WEIGHT	SCALE	REV	
FOR INFORMATION ONLYNOT FOR MANUFACTURING PURPOSES			UV FUSED SILICA	0.001kg		A	