



NOTES/SPECIFICATIONS:

- 1. DESIGN WAVELENGTH: 587.6 nm
- 2. FOCAL LENGTH: f=-75.3 mm ± 1%
- 3. BACK FOCAL LENGTH(REF): bf=-77.7 mm
- 4. CLEAR APERTURE: $> \emptyset$ 22.86 mm
- 5. SURFACE QUALITY: 40-20 SCRATCH-DIG
- 6. CENTRATION: ≤ 3 arcmin
- 7. DIAMETER TOLERANCE: +0.0/-0.1 mm
- 8. THICKNESS TOLERANCE: ±0.1 mm
- 9. SURFACE IRREGULARITY: $\leq \lambda/4$, @633 nm
- 10. PLANO SURFACE FLATNESS: $\leq \lambda/2$, @633 nm
- 11. SPHERICAL SURFACE POWER: ≤ 3λ/2, @633 nm
- 12. COATING(\$1,\$2): BBAR Ravg<0.5% FROM 1050 nm-1700 nm,0°AOI

FOR INFORMATION ONLY NOT FOR MANUFACTURING PURPOSES

DRAWING PROJECTION			客创光科 RCOPTICS			
	NAME	DATE	D25.4mm F=-75mm UVFS	C Coated Plano Concave Lens		
DRAWN	CWD	2022/5/18	PC425475-C			
APPROVAL	ZSB	2022/5/18	MATERIAL	WEIGHT	SCALE	REV
FOR INFORMATION ONLYNOT FOR MANUFACTURING PURPOSES			UV GRADE FUSED SILICA	0. 0052kg		С