

- NOTES/SPECIFICATIONS:

 1. CLEAR APERTURE (\$1, \$2, \$3): >70% OF FACE, LENGTH, AND WIDTH

 2. SURFACE FLATNESS (\$1, \$2, \$3): \(\lambda\)/10 AT 632.8nm

 3. SURFACE QUALITY (\$1, \$2, \$3): 40-20 SCRATCH-DIG

 4. DIMENSION TOLERANCE: ±0.1mm

 5. ANGULAR TOLERANCE: ±3 arcmin


 6. COATING (\$1): -A (350-700nm)

 7. BBAR COATING Ravg<0.5% at 0° AOI

- DIMENSIONS IN mm UNLESS OTHERWISE NOTED 8.

NOTE:

FOR INFORMATIONAL PURPOSES ONLY. NOT FOR MANUFACTURING.



PRAWING PROJECTION	$\bigcirc \bigcirc \bigcirc$		客创光科 RCOPTICS				
	NAME	DATE	N-BK7 RA Prism, 10mm, A Coated on hyp.				
DRAWN	CWD	2022/5/18	PS1010H-A				
APPROVAL	ZSB	2022/5/18	MATERIAL	WEIGHT	SCALE	REV	
FOR INFORMATION ONLYNOT FOR MANUFACTURING PURPOSES			N-BK7		4:1	A	