



NOTES/SPECIFICATIONS:

1. CLEAR APERTURE: $\geq \varnothing 22.86$ mm
2. DIAMETER TOLERANCE: $+0.0/-0.2$ mm
3. THICKNESS TOLERANCE: ± 0.1 mm
4. SURFACE FLATNESS(S1, S2): $<\lambda$ AT 633 nm OVER CLEAR APERTURE
5. SURFACE QUALITY: 40-20 SCRATCH-DIG
6. PARALLELISM: ≤ 1 arcmin

FOR INFORMATION ONLY
NOT FOR MANUFACTURING PURPOSES

| | | | | | | |
|-------------------------------------------------------|------|---------------------------------------------------------------------------------------|---------------------------------------------------------------------------------------|---------|-------|-----|
| DRAWING PROJECTION | |  |  | | | |
| | NAME | DATE | D25.4mm ZnSe Window, 5mm Thick | | | |
| DRAWN | CWD | 2022/5/18 | WG7254-5-1 | | | |
| APPROVAL | ZSB | 2022/5/18 | MATERIAL | WEIGHT | SCALE | REV |
| FOR INFORMATION ONLYNOT FOR MANUFACTURING PURPOSES | | | ZINC SELENIDE | 0.013kg | | B |